



ASHBURN

Cut - Clean - Protect

TECHNICAL DATA SHEET

COLD GALVANIZING COMPOUND AEROSOL

- Will not crack, peel, or yellow even under extreme conditions.
- Dries to a hard film containing pure bonded zinc dust
- Provides excellent adhesion to all metal surfaces
- Dries to a flexible, paintable coating

DESCRIPTION

This product is designed to protect iron and steel surfaces from rust and corrosion. Its high zinc content assures maximum protection on metal surfaces. Dries quickly to a hard film containing pure bonded zinc dust. Provides two way protection, first with the high zinc content protective coating, secondly with true galvanic action. Galvanic action is effective when surface is scratched, broken or dissipated and moisture is present. Dries to a flexible coating that bends without chipping. Compares to a hot dip galvanize when applied as a 3 mil thickness. Can be used as a protective final coating or primer wherever iron or steel will be exposed to atmospheric or corrosive conditions. Formulated for use in presence of moisture, salts and acids.

APPLICATIONS

Areas of use include bus barns, refineries, pipe yards, oil rigs and industrial plants. For iron & steel surfaces, air conditioners, truck & auto fleets, automotive bodies, agriculture equipment, fences, metal roofs, metal buildings, metal fabricators, railroad equipment and marine equipment.

SPECIFICATIONS

FORM: Solvent Base Aerosol

ODOR: Solvent

COLOR: Grey

DETERGENCY: None

TOXICITY: 100 ppm OSHA TLV

WETTING ABILITY: N/A

STORAGE STABILITY: 1 Year

COLD STABILITY: 32° F

PHOSPHATES: N/A

TEMPERATURE TOLERANCE: Continuous 250°F

Intermittent 300°F

FLASH POINT: 60-70° F

FLAME EXTENSION: 18"

SOLUBILITY IN WATER: None

SPECIFIC GRAVITY: 1.00

% VOLATILE BY VOLUME: 66%

pH: N/A

PROPELLENT: Hydrocarbon

EVAPORATION RATE: Moderate

BIODEGRADABILITY: No

PART# M-25700